

**TECHNICAL DATA**  
**DF-2662**  
**100% solids epoxy primer**

**DESCRIPTION**

**DF-2662** is a specially designed, 100% solids clear epoxy primer to be used in conjunction with high performance epoxy and urethane flooring systems.

**RECOMMENDED USES**

- Provides an excellent primed surface for DF-1282 hi-build coating
- 100% solids clear epoxy finish sealer
- An excellent primer for any 2-component epoxy system

**FEATURES**

- Flexible- resists thermal cycles of concrete.
- Promotes excellent bond between substrate and topcoats
- 100% solids, no toxic solvent fumes
- Excellent coverage
- Good penetration
- Excellent chemical resistance
- U.S.D.A. accepted
- Very high strength

## **TECHNICAL DATA**

### **Properties of Part A and Part B**

	<b><u>PART A</u></b>	<b><u>PART B</u></b>
Color	Clear	Amber
Percent Solids	100%	100%
Mix Ratio	2 parts	1 part
Shelf Life	2 years	2 years

To the best of our knowledge the technical data contained herein is true and accurate as of the date of the issuance of said technical data, but is subject to change without prior notice. The user must contact Dynafloor Systems, Inc to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied.

### **Properties of mixed Part A and Part B**

Color	Amber
Gel Time	30-40 minutes
Initial Cure	6-8 hours
Full Cure	28-36 hours

### **Properties of Cured DF-2662**

Compressive strength	12,000-14,000 psi
Tensile strength	5,000-6,000 psi
Splitting Tensile strength	2,000-2,500 psi
Elongation	10%
Water Absorption	0.25 to 0.4%
Chemical Resistance	Excellent